SPECIFICATION



EVERCOOL MODEL TC200-9 Oil Circulating Temperature Control Unit

Heating Capacity: 9 kW
Maximum Operating Temperature: 200°C

Heater Control: Solid State Relay

Cooling Capacity: 20kW

Tank Capacity: 20 litres - stainless steel
Pump Type: Submersible pump
Maximum Flow/Pressure: 60ltr/min @ 3.5 bar

Pump Power: 0.9 kW

Electrical Supply: 400v - 3 ph - 50 Hz + E

Control Voltage: 24v AC

Process Connection IN/OUT: 3/4"
Cooling Connection: 3/4"

Weight: 55 kg

Dimensions: LxWxH 325 x 610 x 700mm

Noise Level: Less than 80 dBA at 1 metre

STANDARD FITTED EQUIPMENT

PID controller

Submersible pump which eliminates internal seal leakage

Non-ferrous internal parts

Low watts density, long life incoloy heating element Large surface area for maximum heat dispersion

Motor protection device

Castors mounted for ease of transport

Automatic filling

Security thermostat for heater element protection

Solid state relay

Optional Extras:

Double water outlet kit
Flow rate control
External sensor
PT100 process sensor
Return of process temperature indication
Manual filling
Serial interface 4-20mA, RS485, 0-10 volts

